

Declaration of performances

DoP N° 0002-06

1. Unique identification code of the product-type:

I02 02

TECH CRIMPED ROLL 1.0 – TECH CRIMPED ROLL 2.0

NAPPE HRM 400 JAUNE - NAPPE SUPER HRM – NAPPE ALU STRUCTUREE

2. Intended use (according harmonised technical specification):

Thermal insulation of Building Equipment and Industrial Installations (ThIBell)

3. Name, registered trade name and contact address of the manufacturer:

Saint-Gobain Isover

12 Place de l'Iris – 92400 Courbevoie

www.isover-marche-technique.fr

4. Name and contact address of the authorised representative:

Not applicable

5. System(s) of Assessment and Verification of Constancy of Performance of the construction product:

AVCP System 1 for Reaction to fire.

AVCP System 3 for other characteristics.

6. a/ Case a construction product covered by a harmonised standard:

EN 14303:2009+A1:2013

Notified Body(ies):

- ACERMI (Notified Body n° 1163) performed the determination of the product-type on the basis of type testing (including sampling); initial inspection of the manufacturing plant and of factory production control; continuous surveillance, assessment and evaluation of factory production control; under system 1. and issued a certificate of constancy of performance according EN 14303:2009+A1:2013
- LNE (Notified Body n°0071) and CSTB (Notified Body n°0679), performed the determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), under system 3. They issued the relevant test reports.

b) Case of a construction product for which a European Technical Assessment has been issued:

Not applicable

Declaration of performances

DoP N° 0002-06

7. Declared performance:

All characteristics listed in the table under are determined in harmonized standard EN14303:2009 +A1:2013

Essential characteristics		Performance				
		TECH CRIMPED ROLL 1.0	NAPPE HRM 400 JAUNE	NAPPE ALU STRUCTUREE	TECH CRIMPED ROLL 2.0	NAPPE SUPER HRM
Reaction to fire - Euroclass Characteristics		A1				
Acoustic absorption index	Sound absorption	NPD				
Thermal resistance	Thermal Conductivity (λ)					
	50°C	0,044			0,042	
	100°C	0,056			0,053	
	150°C	0,072			0,067	
	200°C	0,095			0,083	
	250°C	0,120			0,104	
	300°C	0,150			0,125	
	400°C	-			-	
	Dimension et tolerances	$d_D = 60 \text{ mm} - 100 \text{ mm T3}$	$d_D = 30 \text{ mm} - 100 \text{ mm T3}$	$d_D = 80 \text{ mm T3}$	$d_D = 30 \text{ mm} - 100 \text{ mm T3}$	$d_D = 100 \text{ mm T3}$
Water permeability	Water absorption	WS1				
Water vapour permeability	Water vapour diffusion resistance	MV1				
Compressive strength	Compressive stress or compressive strength for flat products	NPD				
Rate of release of corrosive substances	Trace quantity of ions Cl-	NPD				
	Trace quantity of ions F	NPD				
	Trace quantity of ions SiO_3^{2-}	NPD				
	Trace quantity of ions Na+	NPD				
	Value of ph	NPD				
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD				
Continuous glowing combustion	Continuous glowing combustion (b)	NPD				

Declaration of performances DoP N° 0002-06

Durability of reaction to fire against ageing/degradation	Durability characteristics	(a)	
Durability of thermal resistance against ageing/degradation and against high temperature	Thermal Conductivity	(b)	
	Dimensions and tolerances	See above	
	Dimensional stability, or Maximum Service Temperature	ST(+/250)350	
Durability of reaction to fire against high temperature	Durability characteristics	(c)	
Durability of thermal resistance against high temperature	Durability characteristics	(b)	
	Maximum Service Temperature, Dimensional Stability	ST(+/250)350	

NPD: No performance determined

(a) The fire performance of mineral wool does not deteriorate with time. The Euroclass classification of the product is related to the organic content, which cannot increase with time.

(b) Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gases than atmospheric air.

(c) The fire performance of mineral wool does not deteriorate with high temperature. The Euroclass classification of the product is related to the organic content, which remains constant or decreases with high temperature

- 8. The performance of the product identified in point 1. is in conformity with the declared performance in point 7.**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Christian Bouigeon
General Director Isover
Courbevoie, the 01/05/2021